



# coverstitch blcs

The BLCS is a coverstitch/chain stitch machine that enables sewers to achieve a commercial finish on all dressmaking and home decor projects. The BLCS effortlessly creates triple, wide and narrow coverstitch as well as chain stitch. It offers a professional finish on hems, belt loops, bindings and much more.

The BLCS offers exclusive Baby Lock features like instant Jet Air Threading, tubular looper system, full featured differential feed and the ability chain off for ease of use. The chain off feature can also be used with decorative threads to create beautiful braids.

These features are just some of the many patented features exclusive to Baby Lock. The BLCS Coverstitch is the perfect partner to any overlocker or sewing machine.



# coverstitch blcs

#### **INSTANT JET AIR THREADING:**

Simply push the lever and air blows the thread through the tubular looper! Threading looper made easy by Baby Lock.



Baby Lock makes finishing coverstitch easy with the ability to chain off.

#### **CHAIN & COVER STITCHES:**

The Evolve features a 6mm triple and wide coverstitch, a 3mm narrow coverstitch and a decorative chain stitch.

#### **DIFFERENTIAL FEED:**

A full range differential feed used for gathering and easing as well as compensating for stretch distortion of knit fabrics.

### **OPTIONAL ACCESSORIES:**

- Piping foot 3mm
- Piping foot 5mm
- Gathering foot
- Elasticating foot
- Lace foot
- Double fold bias binders (7/28mm) and (10/36mm)
- Single fold bias binders (7.5/28mm) and (11/40mm)
- Knit binder (8/30mm), (10/36mm) and (15/48mm)
- Plain hemmer 6mm and 12mm
- Single downturn feller 6mm, 16mm and 25mm
- Belt loop folder (10/19mm) and (20/38mm)



### Colour-coded tension system with auto tension release

- The ability to continually chain off for coverstitch
- Tension adjustments on each thread
- Coverstitch using three needles (triple coverstitch)
- Coverstitch using two needles wide (6mm)
- Coverstitch using two needles narrow (3mm)
- Chain stitch using left, centre or right needle position
- Tubular looper prevents thread tangling
- Vertical needle system minimizing needle deflection
- Full range differential feed ranging from 0.6 to 2
- Adjustable stitch length 1mm 4mm
- Snap-on multi purpose foot
- Built in thread cutter
- Built in accessory storage
- Optional range of accessory feet available, piping, gathering, lace, elasticating, etc.
- Optional range of accessories to attach bias binding, form belt loops, hemming, etc.
- Safety switch connected to front door
- 1300 stitches per minute
- Needle system ELx705CF #12/80 #14/90
- 5 year conditional warranty, parts and labour
- Machine weight 7.3kg
- Made in Japan

visit www.babylock.com.au

## 0.8 0.6

• Pintucking foot

• Hemming foot

• Fabric guide

Clear foot



