



Feel Comfort and PowerProfessional Quality Quiltingand Sewing Machine

ашкі

* ax/a 🧃

.....



2.4

Kivei Istrial Technic HZL-UX8

User-focused operabilit



Light control function changes the color temperature of the light





NEW



Adjust the color temperature of the bulb between daylight and soft white. This eliminates visibility difficulties with certain fabric and thread color combinations.

Notification before bobbin thread runs out



JUK

AA/8 (,

An optical sensor will notify you when the bobbin thread reaches a certain amount.Sew with confidence without worrying about the remaining amount of bobbin thread.

11111

NEW



y

Visualization of adjustment values





NEW

NEW



The animation changes according to the adjustment value.

Store recall stitch patterns

The last 10 stitches are stored in the history.



View illustrations of stitch patterns in the history to easily identify and select them with a single touch.



The settings that differ from the defaults are highlighted in blue.

Adjust the presser foot pressure with the easily accessible dial



In addition to the popular stitch width and length adjustments, easily adjust the presser foot pressure with a dial below the touch panel.Being able to change the presser foot pressure while sewing allows you to immediately respond to stretched stitching and uneven feeding.





NEW

Before adjustment

After adjustment

Sew fabrics like knit,fleece,neatly and more without stretching by adjusting the presser foot pressure.

color touch panel can be operated like a smartphone

Just like on a smartphone or tablet, intuitively select and edit patterns, change various settings, and view operation videos. With only the most important and frequently used operations available, the layout and user friendliness of icons, etc., are revolutionary.

Kires Industrial Technology

Have your favorite accessories always at hand



The auxiliary bed with accessory storage is the first among sewing machines with a 12" workspace.Keep your most often used accessories in their place and at your fingertips.

NEW

Make sewing more pleasant

mmm



Using JUKI Smart Feed allows you to reduce uneven feeding and stretched stitching of thin fabric.



Feeding can be stabilized simply by lowering the unit.

Easily switch to straight stitch sewing conditions



Even with a narrow presser foot, the feed dog for straight stitches firmly feeds the fabric to provide smooth handling while sewing edges and curves. Not only prevent the fabric from being pushed into the needle hole at the start of sewing,but realize operability that was only possible with a straight stitch sewing machine, such as sewing edges and sharp curves.

You can easily change the presser foot, feed dog and throat plate to straight stitch versions.



Straight throat plate



Straight feed dog

Enjoy more variations and applications with tapering

NEW

Increased ranges of the angle and direction settings have expanded the possibilities for sewing tapering.



You can select the angle and direction for the beginning and end of tapering.

> You can set a stitch length in advance or store the length of the stitches that were sewn.





By using the memory and inversion functions, star-shaped appliqués can be beautifully finished.

Various presser foot lifting functions

Micro-lifter function





The feed dog lowers automatically when the presser foot is raised to the extra lift position with the knee lifting lever. This prevents the fabric from getting caught on the feed dog and allows the fabric to be taken in and out smoothly.



When micro-lifter function is used



When micro-lifter function is not used Using the presser foot pressure dial, you can raise the presser foot slightly to prevent uneven feeding and achieve a beautiful finish when sewing quilts,velvet,and other fabrics.



Pivot function

This allows you to easily change the sewing direction while leaving both hands on the fabric, for example, when sewing corners of appliqués. (function to automatically raise the presser foot when sewing is stopped with the needle in the lower position)

Beautiful buttonholes surpassing the quality of home sewing machines

Smooth and comfortable free-motion sewing



Buttonhole sewing with clamping plate and sensor

This provides reliable feeding, even on thick fabrics and seams, and automatically corrects the left and right seam densities.

Adjustable cutting width for buttonholes



Since the cutting width can be changed, you can sew a buttonhole that matches not only the button size but also the button thickness.



Transparent quilt presser foot makes the needle visible.



Since the feed dog can be lowered with the push of a button, you can easily set up the machine for free-motion sewing.



Use the included quilt presser foot for free-motion quilting with a ruler (ruler work).* The ruler is an optional accessory.





You can view detailed operating procedures on the sewing machine or with instructional videos on a smartphone





You can view an instructional video on your smartphone by scanning the QR code of the operating procedure that you want to view.

Select the title of the operating procedure that you want to view and follow the step-by-step instructions show in animated video.



Easily combine and recall patterns

Smartphone-like touch panel operations make it very easy to combine one-point patterns and characters. You can also recall (up to 10) previously created patterns after viewing them on the screen.

\$ ** 75 * SC ** 76 DCathy P Million A Million A Million CE & CO CE & CEO

Create multiple variations from a single pattern, such as combining vertical and horizontal inversions.

| SINGLE | Practical RABC | Buttonhole | Appliqué | UI T | Tapering | UI Quilt lin | e 👖 | Scallop | 01 | One-point | 01 | Decorative | 01 | Vintage | 01 | Feather/Lace 🖬 I | | | | | |
|---------------|---|------------|--------------------|--|-----------------------------------|--|--|--|----|---|---|---|--|---|---|---|--|---|---|---|--|
| COMBINATION | | | Appliqué | 01 | | Quilt lin | e 👖 | Scallop | 01 | One-point | 1 1 | Decorative | 01 | Vintage | 01 | Feather/Lace 🖬 | Aa 🛛 | 1 Aa | 01 | Aa | U I |
| <u>COMBIN</u> | 01 022 023 01 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 | | 201 202 203 20 | 205 3 205 3 215 215 215 225 215 225 225 225 | 301 302 303 304 ■ ■ < > 006 | 305 401 402 40 406 407 40 406 407 40 | 3 404 405 3 404 405 409 410 3 414 415 3 414 415 3 414 85 3 414 415 3 416 3 4 | 501 502 503 506 507 508 511 512 511 512 | | One-point GIT GIZ GIZ | 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 | Decorative 71 702 71 71 71 71 71 71 71 71 71 71 71 71 71 | 746 747 748 749 750 | 801 802 803 8 805 807 808 8 806 807 808 8 811 82 8 81 8 81 81 8 81 | 04 805 09 810 14 815 19 ★ 20 14 825 19 ★ 225 14 825 19 ★ 225 14 825 19 ★ 225 19 ★ 225 19 ★ 225 10 | Feather/Lace 11 91 903 904 905 90 | ABCDE FGHI abcde fghi 12345 67890 ÅÅ&ààê coint A&a ABCDE FGHI | <i>風田</i> <i>風田</i> <i>通田</i> <i>通田</i> <i>通田</i> <i>日</i> <i>日</i> <i>日</i> <i>日</i> <i>日</i> <i>日</i> <i>日</i> <i>日</i> | CDE DDE CHCdi i i i i i i i i i i i i i i i i i i | ABCHCL23 FGbcL23 678 678 678 678 678 678 678 678 678 678 | DE 11位です 14日です 14日です 14日の 14日の 14日の 14日の 14日の 14日の 14日の 14日の |
| | | | | 235 | | | | | | 631 632 633 634 635 ** | 681 662 683 684 2.5 2.5 | 731 732 733 734 735 731 732 737 738 739 740 736 737 738 739 740 9 8 8 8 8 741 742 743 744 745 741 742 743 744 745 741 742 743 744 745 741 742 743 744 745 741 742 743 744 745 741 742 743 744 745 741 742 743 744 745 | 716 777 778 779 780 ★ ★ ★ ★ 781 782 783 784 785 ★ ★ ★ ★ ★ 785 784 785 ★ ★ ★ ★ ★ ★ ★ ★ ★ ★ ★ ★ ★ ★ ★ ★ ★ ★ ★ | 831 832 833 83 836 837 836 837 | 34 835 | | a b c d e f s h i 1 2 3 4 5 6 7 8 9 0 Ă A Æ à ĉ å è é ê Ç ç i Ñ ř , . : ; ; | アカキシニン相学 | ラクス三八園交 マオコン五十育組 | サシスカキク | 年保九四七ケエ 組育十五ソコオ |

More fun with optional items! Easy to use with included accessories!

Optional accessories

Easy positioning at the beginning of sewing with the cross LED pointer LED pointer



With the LED pointer, you can start sewing without lowering the needle to check the sewing start position. You can also attach a borescope camera instead of the LED pointer. Part No.40247205



creativity with the LED pointer as a guide when aligning rows of patterns for sewing.



Easily share images and videos you are sewing to social media *Please purchase a commercially available borescope camera.

Mounting base



The mounting base allows you to attach the LED pointer, scope, and magnifying lens attachment to the sewing machine. Part No.40247204



Other optional accessories



Enjoy more three-dimensional decorations with thick threads or ribbons.



It is used when decorative sewing is performed with bobbin thread using thick thread or ribbon.Wrap the thread you want to decorate around the bobbin and draw a pattern with pattern stitching or free motion. Part No.40247203

.

Dedicated hook for thick thread decoration



Put two large spools.



Part No.40247079 Use the mounting base. (Part No.40247204) Use as a magnifying glass to enlarge the needle area.When not in use, you can move it out of the way.



Adapter shank Part No.40207583

presser bar.

Use with a presser foot that is directly attached to the



Quilting presser foot(open type) Part No.40224355

Use the adapter shank.



Smooth presser foot(for JSF) Part No.40248701

The smooth presser foot that can be used for JUKI Smart Feed. Used for difficult materials.

Included accessories

Auxiliary box





Electric knee lifting lever



This highly responsive lever allows the presser foot to be moved up and down with very little force and without taking your hands off the fabric.

Foot controller (with independent foot switch functions) —



The foot switch can be attached to either the left or right side of the pedal.Any one of seven switch operations can be assigned to the foot switch.

Built with you in mind

List of main functions / specifications

| | Name | HZL-UX8 | | | | | | |
|----------------------|---|---|--|--|--|--|--|--|
| Functions | Control System | Computer | | | | | | |
| | Number of stitch patterns | 368 | | | | | | |
| | Number of available fonts | 4 | | | | | | |
| | Buttonhole | Automatic (sensor system) with clamping plate | | | | | | |
| | Start / stop button | Green: Ready to start and / or while sewing Red: Not ready to start Orange: When the lock stitch button is pressed while the sewing machine is engaged in pattern sewing. | | | | | | |
| | Maximum stitch speed | 1,050sti / min | | | | | | |
| | Auto thread trimming | Yes | | | | | | |
| | Automatic needle threader | Automatic needle threader | | | | | | |
| | Thread tension system | Automatic | | | | | | |
| | Automatic lock stitch | Automatic lock stitch and thread trimming | | | | | | |
| | Feed mechanism | Box Feed mechanism | | | | | | |
| | JUKI Smart Feed (dual feed function) | Yes | | | | | | |
| | Presser foot pressure adjustment | Stepless adjustment (digital) | | | | | | |
| | Drop feed | Yes | | | | | | |
| | Easy bobbin winding | Yes | | | | | | |
| | Bobbin thread winder | Bobbin winder with independent motor | | | | | | |
| | Quick bobbin preparation | Yes | | | | | | |
| | Bobbin thread counter | No | | | | | | |
| | Bobbin thread run-out sensor | Yes | | | | | | |
| | Light | 6 LED lights | | | | | | |
| | Function to straight-line stitching | straight throat plate, straight feed dogs and straight presser foot | | | | | | |
| | Micro-lifter | Presser foot pressure settings by dial | | | | | | |
| | Free arm | Yes | | | | | | |
| | | | | | | | | |
| | Change in the length/wide of stitches | Dial system / LCD numerical display Stitch width: Max. 7mm Stitch length: Max. 5mm | | | | | | |
| | Number of needle position (straight stitch/other than srtaight stitch) | 37 / According to pattern | | | | | | |
| | Pattern reverse | Up / Down and left / right | | | | | | |
| | Twin needle sewing | Yes (Twin needle is option) | | | | | | |
| | Elongation Pattern | Yes | | | | | | |
| | Adjustable starting / reverse stitch speed | Yes | | | | | | |
| | Needle up/down button | Yes | | | | | | |
| | Low-speed inching sewing | Yes | | | | | | |
| | Needle stop position switching | Yes | | | | | | |
| | Presser foot pivot function | Yes | | | | | | |
| | Save/call of patterns | 10 patterns | | | | | | |
| | Horizontal presser foot holder button | Yes | | | | | | |
| | Height of lifting of presser foot (1 step / 2 steps) | Button system: 6 · 8 · 10mm / 12mm Lever system: 6mm / 12mm Knee-lifting Lever system: 6 · 8 · 10mm / 12mm | | | | | | |
| | Lock mode | Yes | | | | | | |
| | Operation guide | Displayed as animation and illustrations and text | | | | | | |
| Standard accessories | Sewing machine cover | Soft cover with accessory storage | | | | | | |
| | Auxiliary bed | Yes | | | | | | |
| | Knee-lifting lever | Yes | | | | | | |
| | Wide table | Yes | | | | | | |
| | Foot controller | Yes (with separate foot switch) | | | | | | |
| | Accessory box | Yes | | | | | | |
| | Accessories | Standard presser foot (A) / Straight presser foot(S) / Zipper presser foot (B) / Overcasting presser foot (C) / Bilind stitch presser foot (D) / Buttonhole presser foot (E) / Manual buttonhole presser foot (I) / Open toe presser foot (O) / Patchwork presser foot (P) / 7mm guide foot(7) / Quilt presser foot (for the ruler) (Q) / Edge Sewing presser foot (R) / Straight throat plate / Straight feed dog / Bobbin (4) / Needle set HA x 1 # 11 (1): # 14 (1): # 14 (1): # 16 (1): for knit # 11 (1) / Quilt guide / Auxiliary spool pin / T-shape screwdriver / Ripper / Cleaning brush / Spool cap (large) / Spool cap (Middle) / Spool cap (Small) / Foot Controller / Knee-lifting lever / Power cord / Wide table / Sewing machine cover / Quick Reference Guide / Accessory box | | | | | | |
| Specifications | Dimensions | 602(W)×310(H)×264(D)mm | | | | | | |
| opeemeanons | Arm size | 305x120mm | | | | | | |
| | Weight | 14.9kg | | | | | | |
| | | ITTORY | | | | | | |



2-11-1, TSURUMAKI, TAMA-SHI, TOKYO 206-8551, JAPAN https://www.juki.co.jp



This is an eco-friendly product which complies JUKI ECO PRODUCTS standards for protecting the environment.



The sewing machine complies with the "JUKI Group Green Procurement Guidelines" on the use of hazardous substances, which is stricter than other restrictions, such as those of the RoHS Directive.

For details of JUKI PRODUCTS, refer to: https://www.juki.co.jp/eco_e/index.html

*The RoHS Directive is an EU Directive limiting the use of 6 hazardous substances (lead, hexavalent chromium, mercury, cadmium, PBB and PBDE) in electrical and electronic equipment. The Juki Green Procurement Guideline is the voluntarity established criteria to eliminate not only the aforementioned six substances, but also other ones which also adversely affect the environment.



JUKI CORPORATION holds the rights to change technical specifications without prior notice. 2009(F)