## **COMPARISON CHART**













| Acclaim     Enlighten     Victory     Imagine     Enspire       RevolutionAir Threading - Needles     Y     X     X     X     X       RevolutionAir Threading-Loopers     Y     X     X     X     X     X       ExtraordinAir Threading     X     Y     X     X     X     X       Improved Jet-Air (easier looper threader engagement)     X     X     Y     X     Y       Jet- Air Threading     X     X     X     Y     X     Y       Auto Thread Delivery (ATD) System - No Tension Adjustments     Y     Y     Y     Y     Y     X       Tension System     ~     ~     ~     ~     ~     Micromatic Twin Center       Presser Foot Height     6mm     6mm     6mm     4.5mm     6mm   |  |                       |                     |                     |  |  |
|--|--|-----------------------|---------------------|---------------------|--|--|
| RevolutionAir Threading - Needles  | Four Thread Overlockers                                    | NEW MODEL             | NEW FEATURES        | NEW MODEL           |  | NEW FEATURES                                     |
| Name      |  | Acclaim               | Enlighten           | Victory             | Imagine  | Enspire  |
| ExtraordinAir Threading  | RevolutionAir Threading - Needles                          | Y                     | X                   | Х                   | Х  | Х  |
| March   Marc   | RevolutionAir Threading-Loopers                            | Y                     | X                   | Х                   | Х  | X  |
| ## Air Thread Delivery (ATD) System - No Tension Adjustments  Y Y Y Y Y Y Y X  ## Air Thread Delivery (ATD) System - No Tension Adjustments Y Y Y Y Y Y X  ## Air Thread Delivery (ATD) System - No Tension Adjustments Y Y Y Y Y X  ## Air Thread Delivery (ATD) System - No Tension Adjustments Y Y Y Y X X X X X X X X X X X X X X X  | extraordinAir Threading                                    | X                     | Υ                   | Х                   | Х  | X  |
| Auto Thread Delivery (ATD) System = No Tension Adjustments   | mproved Jet-Air (easier looper threader engagement)        | X                     | X                   | Υ                   | Х  | Υ  |
| Persion System   | et- Air Threading  | X                     | X                   | X                   | Υ  | X  |
| Cension System   | Auto Thread Delivery (ATD) System - No Tension Adjustments | Y                     | Υ                   | Υ                   | Υ  | X  |
| Right side of machine   Back   |  | ~                     | ~                   | ~                   | ~  | Micromatic Twin Cam                              |
| Ighting  | Presser Foot Height  | 6mm                   | 6mm                 | 6mm                 | 4.5mm  | 6mm  |
| Prioral Space 2"   | Position of presser foot lever                             | Right side of machine | back of machine     | back of machine     | back of machine                                  | back of machine                                  |
| Throat Space 5"  | ighting  | 3 x LED               | 3 LED               | 2 x LED             | Standard Globe                                   | 2 LED  |
| Sewing speed (stitches per minute)   | Throat Space 2"  | Υ                     | X                   | X                   | X  | X  |
| Arriable Speed Control   X   | Throat Space 5"  | х                     | X                   | Х                   | Х  | Х  |
| Ax X X X X X X X X X X X X X X X X X X X   | Sewing speed (stitches per minute)                         | up to 1500            | up to 1500          | up to 1500          | up to 1500                                       | up to 1500                                       |
| X Y leave loopers locked slight green lines suits -in Needle Threader - (manual)  X  | /ariable Speed Control                                     | Х                     | X                   | Х                   | X  | X  |
| Suilt-in Needle Threader - (manual)   Suilt-in Needle Threader - (ma   | nee Lift   | X                     | X                   | Х                   | Х  | Х  |
| Suilt-in Needle Threader - (manual)   Suilt-in Needle Threader - (ma   |  |                       | v                   | v                   | v  | v  |
| Full Range 0.6 to 2    |  | X                     | · •                 | •                   | align green lines                                | •  |
| Chain and Coversitich         ~  |  |                       |                     |                     |  |  |
| Wave Stitch         Y         Y         X         X         X           Stitch Length         0.75 to 4mm         1.5 to 7.5mm         7         7         7         7         7         7         7         7         7         7         7         7         7   |  | Full Range 0.6 to 2   | Full Range 0.6 to 2 | Full Range 0.6 to 2 | Full Range 0.6 to 2                              | Full Range 0.6 to 2                              |
| Stitch Length   0.75 to 4mm    |  | ~                     | ~<br>V              | ~<br>               | ~<br>  | ~  |
| Stitch Width Overlocking  1.5 to 7.5mm  1.5  |  | <u>'</u>              | •                   |                     |  |  |
| Stitch Width Expressive  | <del>-</del>   |                       |                     |                     |  |  |
| Rolled Hem - Easy Turn Dial Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y  | <del>-</del>   |                       |                     | 1.5 to /.5mm        | 1.5 to /.5mm                                     |  |
| Foot Included on the Machine  Grooved foot   | ·  |                       |                     | V.                  | V.   |  |
| Built in Thread Cutter  Y Y X X X X X X X X X X X X X X X X X  |  | •                     | •                   | <u>'</u>            | •  | •  |
| Found plate for needle screws  Y  Y  Y  Y  Y  Y  Poptional Feet Available  11  11  11  11  11  11  11  11  11  |  |                       |                     |                     |  |  |
| Suilt in Accessory Storage  Y Y Optional Feet Available Optional Attachments  Needle Type Maximum Number of Threads  Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y   |  | Y                     | <u>'</u>            | <u> </u>            | <del>                                     </del> | <del>                                     </del> |
| Optional Feet Available 11 11 11 11 11 11 11 11 11 11 11 11 11   |  | Y                     |                     |                     |  |  |
| Optional Attachments ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~   |  |                       |                     |                     |  |  |
| Needle Type HAx1SP HAX1 |  |                       |                     |                     |  |  |
| Maximum Number of Threads 4 4 4 4 4  |  |                       |                     |                     |  |  |
|  |  |                       |                     | +                   | +  |  |
| Machine Weight 10.9kg 8.4kg 7.5kg 7.5kg 7.5kg  |  |                       |                     |                     |  |  |
|  | Machine Weight   | 10.9kg                | 8.4kg               | 7.5kg               | 7.5kg  | 7.5kg  |
|  |  |                       |                     |                     |  |  |